

Installation Instructions and User Guide

Freestanding Bath Shroud Covers (Standpipes)

Models Covered:

LEG C, LEG G

Please keep this booklet for future reference.

Installer, when you have read these instructions please ensure you leave them with the user.

Important Safety Information

• Please read these instructions thoroughly and retain for future use.

• All products manufactured and supplied by Bristan are safe provided they are installed, used correctly and receive regular maintenance in accordance with these instructions.

• Remove all packaging and check there are no damaged or missing parts. (See Pack Contents) • Before starting any installation please consider the following:

• Before drilling into walls or floors, check that there are no hidden electrical wires, cables or water supply pipes. This can be checked with the aid of an electronic detector.

- If power tools are used do not forget to: - Wear eye protection
 - Unplug equipment after use

Installation

Standpipes are designed to support taps or mixers near a freestanding bath and conceal the pipework which feeds up from under the floor, to the taps.

NOTE: Installation Instructions are only a guide, and the order in which the installation is carried out may be altered to suit on site conidtions.

1. Identify all components and check for completeness, particulary before arranging fitting. It may be a good idea to cover the taps to protect them from damage during installation.

2. Loosen the grub screws (3) on the standpipes, remove the shrouds (5) and screw them, large diameter uppermost, onto the tails of the taps of mixer. We recommend using a suitable liquid sealant (not supplied) to ensure the tap inlet creates a seal.

3. Decide on the positioning of the taps against the bath, making sure the spout reaches.

4. Mark on the floor the position of the pipe inlets.

2

5. Place the floor plates (1) in the desired position, mark out screw holes, drill and using wall plugs if necessary, screw the plates to the floor.

6. The connectors (6) supplied can be brazed onto 22mm pipe work (not supplied)to create the vertical feed through the shroud to the taps or mixer. Use a suitablelength to allow sufficient movement to aid assembly and to ease further connections below the floor.

7. Slide the standpipes (2) over the vertical pipes ensuring sufficient movement to allow connectors (6) to reach the tails. Use the washer (4) to create a seal between the tap tails and the connector (6).

8. Connect the stand pipes to the water supply under the floorboards using elbows (Not Supplied). Turn the taps on and check all connections for leaks.

9. Screw the standpipes into the floor plates (1). Then secure the taps or mixer in position by locating the shrouds (5) into the top of the standpipes (2) and tightening the grub screws (3).

Pack Contents



Maintenance & Care

Your product has a high quality finish and should be treated with care to preserve the visible surfaces.

All surface finishes will wear if not cleaned properly.

The only safe way to clean your Bristan Stand Pipes is to wipe with a soft damp cloth. Stains can be removed using washing up liquid.

All bath cleaning powders and liquids will damage the surface of your standpipes even the non-scratch cleaners.

3

Issue: D7

Part Number: FI LEG C-G



Bristan Group Ltd. Birch Coppice Business Park Dordon Tamworth Staffordshire B78 1SG Web: www.bristan.com Email: enquire@bristan.com

A Masco Company

At Bristan, we want to make things as easy as possible for our customers. That's why we offer solid guarantees on all our products, effective from the date of purchase, to give you peace of mind. To start your free guarantee simply scan the QR code and register your product. Alternatively visit www.bristan.com/register.



