Accessories Wall Mount Fixings Chrome Plated

8

WMNT10 C



Specification	
Finish/Colour:	Chrome
Main Construction Material:	Brass, ABS
Mounting Type:	Wall Mounted
Plumbing System Suitability:	Suitable for all plumbing systems
Minimum Dynamic Pressure (bar):	0.2 Bar
Maximum Dynamic Pressure (bar):	5.0 Bar
Maximum Static Pressure (bar):	10 Bar
Connection Inlet:	15mm Compression
Connection Outlet:	G 3/4"
Isolation Included:	No
What's Included:	2 x Wall Mounts, 4 x Screws, 4 x Rawl Plugs, 1 x Fitting Instructions

Dimensions (measurements in mm)

Features:

- A fast fit fixing kit that makes it easier to install or replace the shower bar valve
- Enables rigid fixing of exposed bar shower valves to 15mm pipework protruding through cavity wall surface
- Compatible on all bar showers with a 15mm inlet connections
- Brass base construction for a secure fixing to the wall
- G3/4" outlet connections
- Wall Mount 10 is a fast fixing kit that makes it faster to fit, maintain or replace a bar shower by enabling a rigid fixing of an exposed bar shower valves to 15mm pipework

Product Certifications:

For more products, visit our website: <u>http://www.bristan.com</u>



TECHNICAL DATA SHEET





30

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com. * - Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

ø65