HOU 5HBSM C

HOURGLASS Tap Range Hourglass 5 Hole Bath Shower Mixer Chrome



Specification					
Product Type:	Bathroom Taps				
Main Construction Material:	Brass				
Mount Type:	Deck Mounted				
Handle Type:	Lever Handle				
Connection Inlet:	3/4" BSP				
Connection Outlet:	M24 Flow Straightener				
Number of Tap Holes:	5				
Valve/Cartridge Type:	3/4" Ceramic Disc Valve				
Plumbing System Requirements:	Suitable for Nominally Balanced Supply Pressures Only				
Minimum Dynamic Pressure:	0.4 bar				
Maximum Dynamic Pressure:	5.0 bar				
Maximum Hot Water Temperature: °C	65				
Maximum Static Pressure: (bar)	10				
Flow Type:	Single Flow				
Isolation Included:	No				
Check Valve Supplied:	No				

Dimensions (measurements in mm)

Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- Includes 1.75m hose and rubclean anti-limescale handset
- Minimum working pressure of 0.4 bar

Product Certifications:



For more products, visit our website: http://www.bristan.com



112				
		245		
104			130	
157				
157	55	55	55 55	

Flow Rates (I/min)									
System Pressure (bar)	0.4	0.5	1	2	3	5			
HOU 5HBSM C	19.1	21.3	30.8	42.6	54.2	69.97			

TECHNICAL DATA SHEET



