DSC 3HBF C

DESCENT Tap Range Descent 3 Hole Bath Filler Chrome



Specification				
Product Type:	Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever			
Connection Inlet:	3/4" BSP threaded tail			
Connection Outlet:	N/A			
Number of Tap Holes:	3			
Valve/Cartridge Type:	3/4" Ceramic Disc Valve 1/4 Turn			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.4 bar			
Maximum Dynamic Pressure (bar):	5.0 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

Dimensions (measurements in mm)

Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- Minimum working pressure of 0.4 bar

Product Certifications:



WRAS Cert. Number: 2304905 WRAS Expiry Date: 30/04/2028

For more products, visit our website: http://www.bristan.com



60 85 88 88

Flow Rates (I/min)								
System Pressure (bar)	0.4	0.5	1	2	3	5		
DSC 3HBF C (mixed)	17.9	20	28.3	40	49	63.3		

TECHNICAL DATA SHEET



