

# BRG SHCDIV C

## BRIGHT Shower Range Bright Concealed Dual Control Valve + Diverter



### Features:

- 15mm inlet connections
- This shower valve has been designed to fit in any UK wall cavity and therefore only needs a 35mm deep cavity space
- Fitting depth including plasterboard and tiles is 60mm - 75mm
- Minimum cold water supply temperature is 4°C
- Maximum hot water supply temperature is 80°C


### Product Certifications:



WRAS Cert. Number: 2005901  
WRAS Expiry Date: 31/05/2025




For more products, visit our website:  
<http://www.bristan.com>



### Specification

Style:	Contemporary
Finish/Colour:	Chrome
Main Construction Material:	Brass
No of Controls:	2
Shower Type:	Bar
Shower Head Type:	None
Valve/Cartridge Type:	Recessed
Maximum Hot Water Supply Temperature °C:	80
Maximum Static Pressure: (bar)	10
Plumbing System Suitability:	All - Preferably Balanced
Working Pressure Range:	Min. 0.2 Bar, Max. 5.0 Bar
Connection Inlet:	15mm Compression Connections
Connection Outlet:	Open
Isolation Valve Included:	No
Check Valve Included:	No

### Dimensions (measurements in mm)



### Flow Rates (l/min)

System Pressure (bar)	0.2	0.5	1	2	3	5
Outlet 1	6.9	12.8	19	27.6	33	42.49
Outlet 2	6.7	12.5	18.5	27	32.04	41.37

## TECHNICAL DATA SHEET



# BRISTAN

D4