# AR SNK EF BN

# **ARTISAN** Tap Range Artisan Easyfit Mono Sink **Mixer Brushed Nickel**



### Features:

- A contemporary twin lever kitchen tap featuring Top Fix Easyfit technology.
- Unique patented top fix design, for simple installation from above the sink.
- Simply drop and twist the top fix base into the tap hole from above, and lock into place with the Allen key provided.
- Two supplied isolation valves and flexi tails mean you can connect to the water supply at this point and isolate the base.
- Push the tap on to the base and secure into position with the supplied Easyfit tool and screws.
- Everything you need in the box including an Allen key, isolation valves, Top Fix Easyfit base, Easyfit tool and flexi tails
- Swivel spout for easy use
- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- High quality metal fixings for security and durability
- Also available in other finishes.
- 10 year parts and 1 year labour guarantee for peace of mind.

SH

÷

Product Certifications:		-▶  ◄	50		<u> </u>		
WRAS Cert. Number: 2204904 WRAS Expiry Date: 30/04/2027	Flow Rates (I/min)						
Winfied Label	System Pressure (bar)	0.3	0.5	1	2	3	5
	AR SNK EF BN (mixed)	9.3	10.6	16.2	23.5	29.3	38.4
TECHNICAL DATA	5 10 10		B	RE	37		

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.


ARANT

ARANT

\* - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

Specification					
Product Type:	Kitchen Taps				
Main Construction Material:	Brass				
Mount Type:	Deck Mounted				
Handle Type:	Lever Handles				
Connection Inlet:	1/2" BSP Flexible Tails				
Connection Outlet:	M22 Female Aerator				
Number of Tap Holes:	1				
Maximum Fitting Depth (mm):	35mm				
Valve/Cartridge Type:	1/2" Ceramic Disc Valve				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.3 bar				
Maximum Dynamic Pressure (bar):	5.0 bar				
Maximum Hot Water Temperature °C:	60°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single Flow				
Isolation Included:	Yes				

## Dimensions (measurements in mm)



D12