# CHV EFSNK C

# CHIVE Tap Range Chive Easyfit Sink Mixer Chrome



#### Features:

- A contemporary twin lever kitchen tap featuring Top Fix Easyfit technology.
- Unique patented top fix design, for simple installation from above the sink.
- Simply drop and twist the top fix base into the tap hole from above, and lock into place with the Allen key provided.
- Two supplied isolation valves and flexi tails mean you can connect to the water supply at this point and isolate the base.
- Push the tap on to the base and secure into position with the supplied Easyfit tool and screws.
- Everything you need in the box including an Allen key, isolation valves, Top Fix Easyfit base, Easyfit tool and flexi tails
- Swivel spout for easy use
- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- High quality metal fixings for security and durability
- 10 year parts and 1 year labour guarantee for peace of mind.


### Product Certifications:



WRAS Cert. Number: 2106902 WRAS Expiry Date: 30/06/2026

| Specification                     |                                   |  |  |  |
|-----------------------------------|-----------------------------------|--|--|--|
| Product Type:                     | Kitchen Taps                      |  |  |  |
| Main Construction Material:       | Brass                             |  |  |  |
| Mount Type:                       | Deck Mounted                      |  |  |  |
| Handle Type:                      | Lever Handles                     |  |  |  |
| Connection Inlet:                 | 1/2" BSP Flexible Tails           |  |  |  |
| Connection Outlet:                | Flow Straightener                 |  |  |  |
| Number of Tap Holes:              | 1                                 |  |  |  |
| Maximum Fitting Depth (mm):       | 35mm                              |  |  |  |
| Valve/Cartridge Type:             | 1/2" Ceramic Disc Valve           |  |  |  |
| Plumbing System Requirements:     | Suitable for all plumbing systems |  |  |  |
| Minimum Dynamic Pressure (bar):   | 0.3 bar                           |  |  |  |
| Maximum Dynamic Pressure (bar):   | 5.0 bar                           |  |  |  |
| Maximum Hot Water Temperature °C: | 65°C                              |  |  |  |
| Maximum Static Pressure (bar):    | 10 bar                            |  |  |  |
| Flow Type:                        | Single Flow                       |  |  |  |
| Isolation Included:               | Yes                               |  |  |  |

## Dimensions (measurements in mm)



| WRAS Expiry Date: 30/06/2026 | Flow Rates (I/min)    |      |      |     |      |      |      |  |
|------------------------------|-----------------------|------|------|-----|------|------|------|--|
|                              | System Pressure (bar) | 0.3  | 0.5  | 1   | 2    | 3    | 5    |  |
| Water Label                  | CHV EFSNK C (mixed)   | 10.4 | 13.4 | 19  | 26.9 | 32.9 | 42.5 |  |
| TECHNICAL<br>DATA<br>SHEET   | ANTER *               |      | B    | RIS | ST/  | AN   |      |  |

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG, Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com

\* - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.