GWF BASNW C

GLIDE Tap Range Glide Waterfall Basin Mixer without Waste Chrome



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever			
Connection Inlet:	1/2" BSP Flexible Tails			
Connection Outlet:	Stainless Steel Integral Aerator			
Number of Tap Holes:	1			
Valve/Cartridge Type:	35mm Single Lever Cartridge			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.1 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	65°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			

Features:

- Long life ceramic cartridge for added durability and ease of use
- Metal fixing nut for added durability
- Flexible tails included

Product Certifications:



WRAS Certificate No: 1911909 WRAS Expiry Date: 30/11/2024







For more products, visit our website: http://www.bristan.com



Dimensions (measurements in mm)

No





Flow Rates (I/min)								
System Pressure (bar)	0.1	0.5	1	2	3	5		
GWF BASNW C (mixed)	3.3	8.6	12.7	17.9	22.1	28.9		

TECHNICAL DATA SHEET



Isolation Included:

