MSAI BAS GG

Product Type:

Isolation Included:

SAIL Tap Range Metallix Sail Basin Mixer Graphite Glisten



Main Construction Material:	Brass				
Mount Type:	Deck				
Handle Type:	Lever				
Connection Inlet:	M10 x 15mm Flexible Tails				
Connection Outlet:	M24 Flow Limited Aerator @ 5lpm				
Number of Tap Holes:	1				
Valve/Cartridge Type:	35mm Cartridge				
Plumbing System Requirements:	Suitable for all plumbing systems				
Working Pressure Range:	Min 0.2 bar, Max 5 bar				
Maximum Hot Water Temperature: °C	65				
Maximum Static Pressure: (bar)	10				
Flow Type:	Single				

Specification

Bathroom Taps

Features:

- Long life ceramic cartridge for added durability and ease of use
- Metal fixing nut for added durability
- Flexible tails included
- Includes clicker waste

Product Certifications:




For more products, visit our website: http://www.bristan.com



Dimensions (measurements	in	mm)
--------------	--------------	----	-----

No



Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
Without Fitted Flow Limiting Aerator	10.5	16.7	24.2	34.4	42.7	55		
With Fitted Flow Limiting Aerator	5.5	5.5	5.5	5.5	5.5	5.5		

TECHNICAL DATA SHEET



