VAL2 BIB C CD

VALUE Tap Range Lever Bib Taps Chrome With Ceramic Disc Valves



Specification				
Product Type:	Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever			
Connection Inlet:	1/2" BSP			
Connection Outlet:	Flow Straightener			
Number of Tap Holes:	2			
Valve/Cartridge Type:	1/2" Ceramic Disc Valve - 1/4 turn			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure:	0.2 bar			
Maximum Dynamic Pressure:	5.0 bar			
Maximum Hot Water Temperature: °C	65			
Maximum Static Pressure: (bar)	10			
Flow Type:	Single			
Isolation Included:	No			
Check Valve Supplied:	No			

Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Supplied with 3" (76mm) metal lever handles

Product Certifications:



WRAS Certificate No: 250403305 WRAS Expiry Date: 30/04/2030






For more products, visit our website: http://www.bristan.com



Dimensions (measurements in mm)



Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
VAL2 BIB C CD (Hot)	6.4	10.4	14.7	20.6	24.8	32.0		
VAL2 BIB C CD (Cold)	6.7	10.9	15.4	21.1	25.9	33.2		

TECHNICAL DATA SHEET



