CSH EFSNK BB

CASHEW Tap Range Cashew Easyfit Monobloc Sink Mixer Brushed Brass



		res:
_	\sim	raci
	-c	H E S

- Unique patented top fix design, for simple installation from above the sink.
- Simply drop and twist the top fix base into the tap hole from above, and lock into place with the Allen key provided.
- Two supplied isolation valves and flexi tails mean you can connect to the water supply at this point and isolate the base.
- Push the tap on to the base and secure into position with the supplied Easyfit tool and
- Everything you need in the box including an Allen key, isolation valves, Top Fix Easyfit base, Easyfit tool and flexi tails
- Swivel spout for easy use
- Long life 1/4 turn ceramic disc valves for added durablity and ease of use
- High quality metal fixings for security and durability
- Also available in other finishes.
- 10 year parts and 1 year labour guarantee for peace of mind.

Product Certifications:




WRAS Cert. Number: 2109916 WRAS Expiry Date: 30/09/2026




11.8 I/min

Specification						
Product Type:	Kitchen Taps					
Main Construction Material:	Brass					
Mount Type:	Deck					
Handle Type:	Lever					
Connection Inlet:	1/2" BSP Flexible Tails					
Connection Outlet:	Anti-Splash					
Number of Tap Holes:	1					
Maximum Fitting Depth (mm):	35mm					
Valve/Cartridge Type:	1/2" Ceramic Disc Valve					
Plumbing System Requirements:	Suitable for all plumbing systems					
Minimum Dynamic Pressure (bar):	0.5 bar					
Maximum Dynamic Pressure (bar):	5.0 bar					
Maximum Hot Water Temperature °C:	65°C					
Maximum Static Pressure (bar):	10 bar					
Flow Type:	Single					
Isolation Included:	Yes					

Dimensions (measurements in mm)





Flow Rates (I/min)								
System Pressure (bar)	0.5	1	2	3	5			
CSH EFSNK BB (mixed)	3.4	5.6	9.2	11.8	16.7			

TECHNICAL



