AL 3TH WMBAS C

ALTUM Tap Range Altum 3 Tap Hole Wall Mounted Basin Mixer Chrome



| Specification | | | | | | |
|------------------------------------|--|--|--|--|--|--|
| Bathroom Taps | | | | | | |
| Brass | | | | | | |
| Wall | | | | | | |
| Paddle | | | | | | |
| 15mm Compression | | | | | | |
| M18 5lpm Aerator | | | | | | |
| 3 | | | | | | |
| 1/2" Ceramic Disc Valve - 1/4 turn | | | | | | |
| Suitable for all plumbing systems | | | | | | |
| 0.5 bar | | | | | | |
| 5 bar | | | | | | |
| 65°C | | | | | | |
| 10 bar | | | | | | |
| Single | | | | | | |
| No | | | | | | |
| | | | | | | |

Dimensions (measurements in mm)

Features:

- This tap has a flow regulator, which limits the flow of water to 5 litres per minute, reducing the amount of water you use.
- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- 10 year parts and 1 year labour guarantee for peace of mind.
- Also available in other finishes.

Product Certifications:

Water Label

4.56l/min

For more products, visit our website: http://www.bristan.com



| 160-180 |
|--------------------------|
| 45-60 |
| 170-190 \$\frac{1}{30}\$ |
| 100 100 |
| Ø45 Ø45 Ø45 |
| 75 |
| 200 |

| Flow Rates (I/min) | | | | | | | |
|------------------------|------|------|------|------|------|------|--|
| System Pressure (bar) | 0.5 | 1 | 2 | 3 | 4 | 5 | |
| AL 3TH WMBAS C (hot) | 3.06 | 4.14 | 4.56 | 4.62 | 4.62 | 4.68 | |
| AL 3TH WMBAS C (cold) | 3 | 4.02 | 4.5 | 4.56 | 4.62 | 4.68 | |
| AL 3TH WMBAS C (mixed) | 3.18 | 4.26 | 4.56 | 4.62 | 4.62 | 4.68 | |

TECHNICAL DATA SHEET





Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances.

Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.